

# HEATSHRINK HEAVY WALL ADHESIVE LINED

**SPECIFICATION  
SHEET:**  
#UTHHWAL.01



## Heatshrink Heavy Wall Adhesive Lined

HWHS heavy wall Heatshrink tubing provides maximum reliability for insulation of cable joints. Manufactured with adhesive lining, HWHS has outstanding sealing and shrinkage properties, and excellent mechanical performance. Applications include underground joints, low voltage terminations and gland and lug sealing.

- 3:1 shrink ratio
- UV resistant
- Operating temperature -55° - 110°C
- Shrink temperature 120°C
- RoHS compliant
- Excellent sealing and insulation properties
- Superior mechanical properties

Product Code	Internal Diameter (mm) As Supplied	Internal Diameter (mm) After Recovery	Wall Thickness as Recovered (mm)	Standard Length	Colour
UTHSHWL 9.0	9	3	2.0	1.2m	Black
UTHSHWL 15.0	15	4	2.4	1.2m	Black
UTHSHWL 24.0	24	6	2.5	1.2m	Black
UTHSHWL 33.0	33	8	3.2	1.2m	Black
UTHSHWL 48.0	48	12	4.3	1.2m	Black
UTHSHWL 56.0	56	16	4.3	1.2m	Black
UTHSHWL 75.0	75	20	4.2	1.2m	Black
UTHSHWL 95.0	95	25	4.2	1.2m	Black
UTHSHWL 130.0	130	36	4.2	1.2m	Black